

FerroSorp SK®
H₂S Removal Media**PRODUCT DESCRIPTION**

FerroSorp® SK is a product based on Iron (III) Oxide-Hydroxide, FeO(OH), that is used for the desulfurization of gases and air. The use of special granulating and drying methods in the production of FerroSorp® SK creates a high form stability, abrasion hardness, and reactivity.

TYPICAL APPLICATIONS

FerroSorp® SK is used for desulfurization of gas with relative humidity in the range of 60-100%. Applications include treatment of gas from landfills and anaerobic digesters.

**TYPICAL CHEMICAL
COMPOSITION (%WT)**

Iron (III) Oxide-Hydroxide

FeO(OH)

TYPICAL PROPERTIES

PRODUCT CODE	FS24P-SK
Particle Size Diameter (mm)	2-4
Particle Size Length (mm)	2-8
Particle Type	Pellet
Bulk Density (lb/ft ³) [(kg/m ³)]	41 +/- 3 [660 +/- 50]
Solid Content	> 80%
Particle Size Distribution (diameter):	
< 2mm	< 10%
> 4mm	< 20%

PACKAGING

FerroSorp® SK is packaged in 2200 lb super sacks.

HANDLING & STORAGE RECOMMENDATIONS

For prolonged storage (> 2 months), protect FerroSorp® SK super sacks from the sun. We recommend that you rotate stock so oldest material is used first.

HEALTH & SAFETY INFORMATION

Health and safety information is available on our product SDS, which can be downloaded from our website interraglobal.com or by contacting Interra Global at 847.292.8600.